



ADSL 2/2+ compliant modem for faster ADSL speeds and extended distances at which high-speed data can be delivered

High-speed "always-on" Internet access

ADSL modem plus router supports up to 253 concurrent Internet users

Advanced security from hacker attacks with Stateful Packet Inspection (SPI) and Network Address Translation (NAT) firewalls

Works with all popular ADSL services

Fast and easy installation with auto configuration

Two phone jacks, including one filtered jack to support an attached telephone

Software upgradeable

Ethernet interface for use with most operating systems

USB interface for connection to Windows computers

Works great with wireless access points

SNMP support (Simple Network Management Protocol)

Documentation and software provided in Danish, Dutch, English, French, Portuguese, and Spanish

Two year warranty



Zoom ADSL X4

**ADSL 2/2+ Modem + Gateway + Router + Firewall
with Ethernet and USB Interfaces**

Model 5651

The Zoom Model 5651 ADSL X4 is a full-rate ADSL 2/2+ modem and a powerful gateway/router/firewall in a single affordable product.

The Model 5651 X4 delivers up to 24 Mbps data speeds over existing telephone wires and is suitable for use in homes or small offices. The Model 5651 is compatible with older ADSL protocols as well as the new ADSL 2/2+ standards for higher data speeds and extended distances at which high data rates can be delivered.* The Ethernet interface on the X4 provides connection to a computer running most operating systems, including Windows 95, 98, 98SE, 2000, XP and Me as well as Linux, Unix and Mac Operating system. The X4 can also be plugged into a hub or wireless access point to provide concurrent Internet access for up to 253 networked computers. The USB port supports connection to a Windows computer.

Security features include Network Address Translation (NAT), and Stateful Packet Inspection (SPI). The NAT firewall hides computers on the local area network from uninvited access through the Internet. SPI assesses the protocol and packet addresses being received to determine if the information should be passed through the firewall to the connected computers. SPI and NAT protect against Internet worms and Denial of Service attacks, some of the most publicized forms of malicious intrusion from the Internet.

Setup is easy using any authorized local or remote computer's Web browser and the intuitive graphical user interface. An auto configuration option automatically establishes the protocol and encapsulation used by the ADSL service. Simple Network Management Protocol (SNMP) is supported for remote maintenance by network administrators.

Zoom ADSL gateways are backed by a two year warranty and over 27 years of experience in the design and support of communication products.

Specifications

ADSL Compliance

- Compliant with ADSL standards:
 - Full-rate ANSI T1.413 Issue 2, G.hs (6.944.1) and ITU G.dmt (G.992.1) standards
 - Splitterless G.lite (G.992.2) specification
 - Annex A
- Compliant with ADSL 2 standards:
 - G.dmt.bis (ITU G.992.3)
 - ADSL Annex L (reach extended DSL)
- Compliant with ADSL 2+standards:
 - G.992.5
- DMT modulation and demodulation
- Full-rate adaptive modem
 - Maximum downstream rate of 24 Mbps
 - Maximum upstream rate of 1024 Kbps
- Supports splitterless ADSL implementation
- Interoperable with all major DSLAM manufacturers

ADSL X4

ADSL 2/2+ Modem + Gateway
+ Router + Firewall with
Ethernet and USB Interfaces

Model 5651

Specifications (continued)

ATM Protocols	<ul style="list-style-type: none">• WAN mode support: PPP over ATM (RFC 2364) and PPP over Ethernet (RFC 2516)• LAN mode support: bridged/routed IP over ATM (RFC 1483) and Classical IP over ATM (RFC 1577)• ATM Forum UNI 3.1/4.0 PVC• Up to eight virtual circuits• ATM segmentation and re-assembly• ATM AAL5 (adaption layer type 5)• OAM F4/F5
Bridge Mode	<ul style="list-style-type: none">• Ethernet to ADSL self learning - Transparent Bridging (IEEE 802.1D)• Supports up to 128 MAC learning addresses
Router Mode	<ul style="list-style-type: none">• Static routing• DNS Proxy• Port Forwarding• DHCP (Dynamic Host Configuration Protocol) server, client, and relay• NAT (Network Address Translation)• NAPT (Network Address and Port Translation)• RIP V1 and V2• PPP Half Bridge• Dynamic DNS• Virtual Server/DMZ Support• Simultaneous USB and Ethernet operation
Security	<ul style="list-style-type: none">• Stateful Packet Inspection (SPI)• User authentication for PPP• PAP (Password Authentication Protocol)• CHAP (Challenge Authentication Protocol)• Password protected system management• VPN passthrough: PPTP, L2TP, IPsec tunnel• Bridge filtering• IP filtering• Blocked Protocols• Black Lists• Attack Protection• Dos Protection
Management	<ul style="list-style-type: none">• Password security• SNMP Version 2.0• Auto configuration• Universal Plug and Play (UPnP)• Remote and local command line or HTTP interface configuration• Software upgradeable firmware through HTTP interface• ATM traffic management functions support UBR, CBR, rt-VBR, nrt-VBR in accordance with ATM forum TM4.1• Loads setup from a file for easy input of a service provider's configuration
Ethernet Interface	<ul style="list-style-type: none">• IEEE 802.3 compliant• Auto-sensing 10/100 BaseT - RJ45
USB Interface	<ul style="list-style-type: none">• Compliant with USB Specification, Revision 1.1• Full-speed USB (12 Mbps)
HTML Graphic User Interface	<ul style="list-style-type: none">• HTTP Graphical User Interface• Password protected access• Firmware upgrades• WAN and LAN side connection statistics• Configuration of static routes and routing table• Firmware upgrades• Configuration of NAT/NAPT• Selection of bridge or router mode• PPP user ID and password• Configuration of virtual circuits
Status Indicators	<ul style="list-style-type: none">• Link - reports Internet connection• LAN - LAN activity• USB - USB connection established• PWR - power on/off
Warranty	<ul style="list-style-type: none">• 2 years
Size	<ul style="list-style-type: none">• 14.6cm x 11.2cm x 2.8cm (5.7 inches x 4.4 inches x 1.1 inches)
Regulatory Approval	<ul style="list-style-type: none">• CE, UL, C-UL, FCC Part 15B, FCC Part 68, CS-03

Specifications

- A computer with an Ethernet port and any operating system that supports TCP/IP (Windows, Mac, Linux, or other).

Package contents:

- Ethernet/USB modem
- Ethernet cable
- USB cable
- Phone cable
- CD ROM
- User Manual
- Power Adapter
- Filters and phone adapters:
Filters and/or phone adapters may be included in some markets. Please check the package for specifics or ask your dealer. An ADSL filter allows a telephone, facsimil machine, or other telephone instrument to be used even when you are online with your ADSL modem.



International Headquarters

Zoom Technologies, Inc.
207 South Street
Boston, MA 02111
USA
Tel: 617 423-1072
Fax: 617 423-3923
email: sales@zoom.com
www.zoom.com
Nasdaq: ZOOM

European Sales/Support

Zoom Technologies, Inc.
Central House
2 Kings Road
Fleet, Hants
GU51 3AD UK
Tel: +44 (0) 1252 582000
Fax +44 (0) 1252 617920

©2005 Zoom Technologies, Inc.,
207 South Street, Boston, MA 02111 USA
Zoom is a registered trademark of Zoom
Technologies, Inc. Windows 98, Windows
Me, Windows 2000, Windows NT4.0 and
Windows XP are registered trademarks of
Microsoft Corporation.
All other registered trademarks and
trademarks used herein are the property
of their respective holders.

* ADSL 2/2+ requires support from your Internet Service Provider

2865 5651